# Large Control Filter

The Large Control Filter has a high capacity and a large screening area. It is used where control fluid might be dirtier than is usual, and the standard control filter would be inadequate.

This larger control filter increases the valve system reliability, and prevents a false operation of deluge systems that might occur due to a clogged control priming line.

# **Materials**

# **Standard Construction**

- Body: Carbon Steel, Red Epoxy coated
- Covers: Brass
- Stem & Nut: Stainless Steel 304Filter Discs: Polypropylene, 60 mesh
- Gaskets: NBR O-rings



- Body: Stainless Steel 316
- Covers: Stainless Steel 316
- Stem & Nut: Stainless Steel 316
- Filter Discs: Polypropylene, 60 mesh
- Gaskets: NBR O-rings

# **NAB Construction**

- ■Body: Ni-Al-Bronze ASTM B148 C95800
- Covers: Ni-Al-Bronze ASTM B148 C95800
- Stem: Ni-Al-Bronze
- Nut (dry): Stainless Steel 316
- Filter Discs: Polypropylene, 60 mesh
- Gaskets: NBR O-rings

## Max Temperature

■ Water: 180°F (80°C)

## Pressure Rating

■365 w psi (25 bar)

#### **End Connections**

■3/8" NPT (F)

## Weight

2.7 kg (6 lbs.)



(for illustration only)



